

ECO-WRAP™

Irrigate more efficiently than blank dripline with fleece-wrapped dripline.

KEY BENEFITS

- Perfect for narrow areas that are difficult to irrigate with standard methods
- Anti-siphon feature and fleece wrap protect against debris and root intrusion
- Saves 20-40% more water than standard products due to superior capillary movement of water to the entire root zone, promoting healthier root growth
- Non-draining, pressure-compensating emitters open/close simultaneously, maximising efficiency
- Check height of 1.5 m minimises system drainage and runoff

PRODUCT SPECIFICATIONS

- Flow rate: 2.1 l/hr
- Emitter spacing: 30 cm
- Tubing dimensions: 0.660" x 0.560" (outside/inside diameter)
- Roll length: 16 mm = 100 m; 17 mm = 90 m
- Accepts 16 mm barb or LOC Fittings

OPERATING SPECIFICATIONS

- Operating range: 1.0 to 3.5 bar; 100 to 350 kPa
- Minimum filtration: 120 mesh; 125 microns
- Air relief recommended for sloping conditions greater than 1.5 m
- Recommended installation depth: turf (10-16 cm); other (10-30 cm)
- Compatible with the Eco-Mat System
- Warranty period: 5 years

MAXIMUM RUN LENGTH FOR ECO-MAT AND ECO-WRAP

| Pressure (bar; kPa) | Length (m) |
|------------------------|---------------|
| 1.0; 100 | 52 |
| 1.5; 150 | 75 |
| 2.0; 200 | 95 |
| 2.5; 250 | 106 |
| 3.5; 350 | 126 |
| 4.0; 400 | 130 |



Eco-Wrap


ECO-WRAP

| Model | Description |
|-------------|--|
| ECO-WRAP-16 | PLD (16 mm) fleece drip wrap, 100 m roll |
| ECO-WRAP-17 | HDL (17 mm) fleece drip wrap, 75 m roll |

Eco-Wrap Installed



Compatible with:



Soil-Clik



Eco-Indicator